

Here are the instructions to access the Classic interface with IUCLID 6.5

- For **Server and ECHA Cloud Services** installations
 - The classic interface, also known as the IUCLID client, can be started using an address of the form:

For IUCLID 6 v5 (October 2020 release and December 2020 patch release)
`http(s)://<server_name>/webstart/classic.jnlp`

Since IUCLID 6 v5.15.0 (April 2021 release)
`http(s)://<server_name>/webstart/oldui.jnlp`
 - Please note that as before, you will need Java Webstart installed on your computer in order to start the classic interface.

- For **Desktop** installations
 - The prelaunch window of the Desktop version shows only the button for opening the web interface, by default
 - Close IUCLID before following the next steps to re-activate the access to the classic interface
 - To get the option of starting the classic interface, a text should be added to the file `client.settings.properties` stored in the following folder of your IUCLID installation folder, on your computer:
`<installation_directory>\glassfish4\glassfish\domains\domain1\config`
 - This file can be edited with a text editor, and the new line shown below should be added:

For IUCLID 6 v5 (October 2020 release and December 2020 patch release)

`use.classic.IUCLID.user.interface=true`

Since IUCLID 6 v5.15.0 (April 2021 release)

```
use.old.IUCLID.user.interface=true
```

- For this change to take effect, the content of the following folder should be deleted:

```
<installation_directory>\glassfish4\glassfish\domains\domain1\osgi-cache\*
```

- After this, please restart IUCLID, after which the option to start the classic interface will be shown